



**D1 CAPACITORS WITH A CAN DIAMETER OF 35...60 mm**  
**D2 CAPACITORS WITH A CAN DIAMETER OF 65...75 mm**

Can material ..... aluminium  
 Base mounting stud ..... see chart  
 Lid ..... plastic with rubber sealing, flanged can  
 Terminals ..... dual tab connectors 6.3 × 0.8 mm  
 ..... (tinned steel, riveted)  
 I<sub>max</sub> (Terminals) ..... 16 A  
 Degree of protection ..... IP 00  
 Humidity class ..... F

**D1 KONDENSATOREN MIT GEHÄUSEDURCHMESSER 35...60 mm**  
**D2 KONDENSATOREN MIT GEHÄUSEDURCHMESSER 65...75 mm**

Gehäusematerial ..... Aluminium  
 Bodenschraube ..... siehe Tabelle  
 Deckel ..... Kunststoff, Bördelverschluss mit  
 ..... Gummidichtung  
 Anschlüsse ..... Doppelflachstecker 6.3 × 0.8 mm  
 ..... (verzinneter Stahl, genietet)  
 I<sub>max</sub> (Anschlüsse) ..... 16 A  
 Schutzgrad ..... IP 00  
 Feuchteklasse ..... F

D <sub>1</sub>	a	B	K	L
35	13.5	M8 × 10 (5Nm)	6.5	6.5
40	13.5	M8 × 10 (5Nm)	9	6.5
45	13.5	M8 × 10 (5Nm)	10	6.5
50	13.5	M12 × 16 (7Nm)	10	6.5
55	13.5	M12 × 16 (7Nm)	10	6.5
60	13.5	M12 × 16 (7Nm)	10	6.5
65	16.5	M12 × 16 (7Nm)	10	8

