

E12./E33.***

AC

420...640V AC/300...450Vrms

C _N (μF)	R _S (mΩ)	L _e (nH)	R _{th} (K/W)	I _{max} (A)	Î (A)	D × L ₁ (mm)	Design options		m (kg)	part no. Bestell-Nr.	pcs./box Box	Approval marks Prüfzeichen			
							1	2							
U _{NAC} 640V		Urms 450V				U _{BB} 970Vrms		U _{BG} 3000Vrms							
10	8.2	80	19	11	200	35 × 68	E2	D1	0.07	E33.D68-5010...	50/FB4	•		•	
12	9.8	80	16	11	196	35 × 78	E2	D1	0.09	E33.D78-5012...	50/FB3	•		•	
14	8.8	80	14	12	228	40 × 78	E2	D1	0.11	E33.E78-5014...	36/FB3	•		•	
15	12.2	90	14	10	191	35 × 93	E2	D1	0.10	E33.D93-5015...	50/FB3	•		•	
16	11.6	90	14	11	204	35 × 93	E2	D1	0.10	E33.D93-5016...	50/FB3	•		•	
16	8.0	80	14	13	261	40 × 78	E2	D1	0.11	E33.E78-5016...	36/FB3	•		•	
18	7.4	80	14	13	293	40 × 78	E2	D1	0.11	E33.E78-5018...	36/FB3	•		•	
20	9.8	90	12	12	255	40 × 93	E2	D1	0.11	E33.E93-5020...	36/FB3	•		•	
25	13.5	100	9.4	12	233	40 × 119	E2	D1	0.17	E33.E19-5025...	36/FB1	•		•	
25	8.4	90	11	14	318	45 × 93	E2	D1	0.15	E33.F93-5025...	36/FB3	•		•	
28	12.4	100	9.4	12	261	40 × 119	E2	D1	0.17	E33.E19-5028...	36/FB1	•		•	
30	11.8	100	9.4	13	280	40 × 119	E2	D1	0.17	E33.E19-5030...	36/FB1	•		•	
30	7.4	90	11	15	382	45 × 93	E2	D1	0.15	E33.F93-5030...	32/FB3	•		•	
35	10.6	100	8.3	14	326	45 × 119	E2	D1	0.20	E33.F19-5035...	32/FB1	•		•	
37	10.1	100	8.3	14	345	45 × 119	E2	D1	0.20	E33.F19-5037...	32/FB1	•		•	
40	9.6	100	8.3	15	373	45 × 119	E2	D1	0.20	E33.F19-5040...	32/FB1	•		•	
45	8.9	100	7.2	16	420	50 × 124	E2	D1	0.30	E33.G24-5045...	21/FB1	•		•	
50	8.3	100	7.2	16	466	50 × 124	E2	D1	0.30	E33.G24-5050...	21/FB1	•		•	
60	9.8	120	6	16	559	50 × 148	E2	D1	0.35	E33.G48-5060...	21/FB0	•		•	
60	6.9	100	6	16	642	60 × 124	E2	D1	0.45	E33.K24-6060...	18/FB1	•		•	
65	8.5	120	5	16	573	60 × 148	E2	D1	0.50	E33.K48-6065...	18/FB0	•		•	
80	7.6	120	4.6	16	705	65 × 148	-	D2	0.55	E33.L48-6080...	10/FB0	•		•	
100	7.2	120	4.6	16	768	65 × 148	-	D2	0.55	E33.L48-5100...	10/FB0	•		•	



E1/E2



D1/D2

Design Options:

E1/E2 (1 x Tab 6.3mm): ...15/220001

D1/D2 (2 x Tab 6.3mm): ...25/220001



E1/E2



D1/D2

